

CHAVE PARA MANDRIL

Tipo «Jacobs» (ASA)

Chave usinada e temperada conforme norma DIN 6349.

Acabamento oxidado preto.

REF.	Modelo	Emb.	Mandril	Capacidade	P. Médio (kg)
CJ-610	K-0	12	0 - 0B	5/32"	0,02
CJ-611	MC-1/S-14	12	kg (p/fur.manual)	1/4"	0,02
CJ-612	K-1 / S-7	12	1A-1B	1/4"	0,02
CJ-613	K-2 / S-17	12	2A-2B	3/8"	0,04
CJ-614	K-3 / S-10	12	14N/34/34B - 3A/3B	1/2"-5/8"	0,08
CJ-615	K-4 / S-13	12	16N - 18N/36/36B	5/8"-3/4"	0,15
CJ-616	K-5	06	20M	1"	0,30
CJ-617	K-7 / S-18	12	7 - 7B	1/4"	0,03
CJ-618	K-30 / S-8	12	30 - 30B	1/4"	0,06
CJ-619	K-32 / S-9	12	32/32B - 33/33B	3/8"-1/2"	0,06



Tipo "Röhm" (DIN 6349)

REF.	Mod.	Emb.	Mandril	Capacidade	P. Médio (kg)
CR-641	S-1	25	4P/6P/8L	5/32"-1/4"-5/16"	0,02
CR-643	S-2	25	8P/10M/10L/10P/10S/13M/13L/13S	5/16"-3/8"-1/2"	0,05
CR-644	S-3	25	13P/16L/16M/16P/16S	1/2"-5/8"	0,14
CR-645	S-4	12	20P/26P	3/4"-1"	0,16